Docket No.: SONYJP 3.0-088 Application No.: 09/438,630

Listing of Claims:

1 10. (canceled)

- 11. (New) A television receiver comprising:
- a receiver section for receiving digital television (a) signals;
- a digital interface for receiving digital television (b) signals reproduced and transmitted from an external storage device; and
- and on-screen display processor for generating an on-(c) scheen display signal from said digital television signals received from said receiver section and from said external storage device, said on-screen display processor being adapted to generate a first on-screen signal representing a description display television program currently received by said receiver second on-screen display а section and representing a description of television programming which is transmitted by said external storage device through said digital interface.
- 12. (New) The television receiver according to claim 11, wherein said first and second on-screen display signals are substantially the same.
- (New) The television receiver according to claim 11, wherein said digital television signals received by said receiver section in clude television program guide information.
- 14. (New) The television receiver according to claim 13, reproduced digital television signals wherein said transmitted from said external storage device include television program guide information.

Application No.: 09/438,630 Docket No.: SONYJP 3.0-088

PS/ Och Cont (New) The television receiver according to claim 14, wherein said on-screen display processor processes said television program guide information included in said reproduced digital television signals to generate said second on-screen display signal and omits unnecessary information from the television program guide information.

- 16. (New) A method of displaying on-screen display signals comprising:
 - (a) receiving digital television signals in a television receiver;
 - (b) receiving digital television signals reproduced and transmitted from an external storage device in said television receiver via a digital interface;
 - (c) generating a first on-screen display signal representing a description of a television program currently received by said receiver; and
 - (d) generating a second on-screen display signal from said digital television signals received from said external storage device through said digital interface representing a description of television programming which is transmitted by said external storage device.
- 17. (New) The method according to claim 16, wherein said first and second on-screen display signals are substantially the same.
- 18. (New) The method according to claim 16, wherein said digital television signals received by said receiver include television program guide information.

Application No.: 09/438,630

Docket No.: SONYJP 3.0-088

19. (New) The method according to claim 18, wherein said digital television signals reproduced and transmitted from said external storage device include television program guide information.

- (New) The method according to claim 19, further 20. comprising processing said television program guide information included in said reproduced digital television signals to omit generate said second on-screen display signal information from the television program quide unnecessary information.
- 21. (New) A method of displaying on-screen displays comprising:
 - (a) generating a first on-screen display by a receiver upon user request when a receiver is currently receiving broadcast television programming, said first on-screen display including a first set of indicia elements representing a description of the television programming currently received by the receiver; and
 - generating a second on-screen display by the receiver (b) upon user request when said receiver is currently receiving television programming transmitted by an external storage device connected to said receiver via digital interface, the second on-screen display of indicia including second set elements description of the television representing а programming transmitted by said external storage device to said receiver, said second set of indicia elements being substantially similar to said first set of indicia elements, but wherein at least one of said first and second sets of indicia elements includes one

Application No.: 09/438,630 Docket No.: SONYJP 3.0-088

on more distinguishing indicia elements to indicate to user the input source of the television the programming being received by said receiver.